Via Facsimile to: 703-872-9306

16 June 2004

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

- 1-5 (canceled)
- 6. (original): A method for selective peening of a coil spring that comprises metal wire and has an inner coil spring diameter, an outer coil spring diameter, a coil spring pitch, and a coil spring length along a coil spring axis, the method comprising
  - providing a peening mask for selective peening of said coil spring, said peening mask comprising
    - a cylindrical inner shield having a diameter slightly less than said inner coil spring diameter and a length not less than said coil spring length; and
    - a coiled outer shield having an inner diameter slightly greater than said outer coil spring diameter and having a pitch substantially equal to said coil spring pitch; and
  - inserting said cylindrical inner shield within the coil spring to form a first assembly;
  - inserting said first assembly within said coiled outer shield to form a second assembly;
  - aligning said cylindrical inner shield and said coiled outer shield with the coil spring; and
  - peening said second assembly.

Via Facsimile to: 703-872-9306

16 June 2004

7. (original): A peening mask for selective peening of a coil spring that comprises metal wire and has an inner coil spring diameter, an outer coil spring diameter, a coil spring pitch, and a coil spring length along a coil spring axis, said peening mask comprising a cylindrical inner shield having a diameter slightly less than said inner coil spring diameter and a length not less than said coil spring length; and a coiled outer shield having an inner diameter slightly greater than said outer coil spring diameter and having a pitch substantially equal to said coil spring pitch.